



Postpure PP™ Graded Density Pleated Polypropylene Depth Media Filter Cartridge

- Composed of graded-density, pleated, polypropylene depth media for high efficiency postfiltration of DI resin applications
- FDA Listed Materials - Manufactured from materials which are FDA listed for food contact applications in Title 21 of the U.S. Code of Federal Regulations.
- Toxicity - All polypropylene components meet the specifications for biological safety as per the USP for Class VI-121 °C plastics (gaskets/O-rings excluded).
- Cartridges are free of resins, binders and adhesives.

SPECIFICATIONS

Dimensions

Diameter (OD) 2.6" (6.6 cm)
 Length (in) 10, 20, 30

Materials

Cartridge Polypropylene caps, core and cage
 Media Pleated, non-woven melt blown polypropylene
 Seals Silicone o-rings and gaskets

Operating Parameters

Maximum Temperature 150°F (65°C) @ 40 psid (2.8 bard)
 Maximum Differential Pressure @ 20°C 75 psid (5.1 bard)
 Filtration Efficiency nominal 90%

Recommended Water Flow Rates


0.3 – 1 micron 2.0 gpm/10" length (7.6 lpm/10" length)
 3 – 30 micron 8.0 gpm/10" length (30.1 lpm/10" length)

Sanitizing Agents

Chlorine, hydrogen peroxide, in-line with hot water (82°C) for one hour, autoclaved for 20 minutes at 121°C under no load conditions.

Sterilization

Multiple autoclaving for 30 minutes at 250°F (121°C) under no end load conditions. In-line steam sterilization is not recommended. May be in-line sanitized with hot water at 180°F (82°C) for 1 hour.



ORDERING INFORMATION

Catalog Number and Description

FCPP	All polypropylene, pleated, nominal depth filter cartridge
X	Cartridge Code: 0 = 2-222 o-rings 5 = 2-222 w/spear 7 = 2-226 o-rings locking tabs w/spear 1 = single open end w/internal o-ring F = double open end w/flat gasket seal
XX	Length (in): 10 = 10, 20 = 20, 30 = 30
XX	Micron Rating: S3 = 0.3 μm, S6 = 0.6 μm, O1 = 1 μm, O3 = 3 μm, O5 = 5 μm, O10 = 10 μm, O30 = 30 μm

To determine your catalog order number, replace the X with one of the numbered or lettered options beside it. Note: Not all part number combinations are available; consult Technical Support for assistance.

LENNTECH

info@lenntech.com

www.lenntech.com

Tel. +31-152-610-900

Fax. +31-152-616-289