


# Testomat 2000® CLF

**LENNTECH**

info@lennotech.com Tel. +31-152-610-900

www.lennotech.com Fax. +31-152-616-289



The process-photometer **Testomat 2000® CLF** is a wet-chemical online instrument for monitoring the content of free chlorine (CLF) in the 0–2.5 mg/l (ppm) range.

## Application

- monitoring of chlorination systems for drinking water/swimming pool water
- protection for reverse osmosis membranes
- monitoring of biocides and conditioning agents containing chlorine

## Measuring range

Free chlorine 0.00 - 0.99 mg/l and 1.0 - 2.5 mg/l

## Technical Data

**Power supply:** 230–240 VAC, 115 VAC, 24 VAC all 50–60Hz

**Power consumption:** max. 30 VA

**Protection class:** I

**Degree of protection:** IP 65

**Ambient temperature:** 10–45 °C, 50 - 104°F

**Option:** booster pump see accessories

**Dimensions (B x H x T):** 380 x 480 x 280 mm

**Weight:** approx. 9.5 kg

**Menu languages:** German, English, French, Italian (others upon request)

## Mains water supply

**Operating pressure:**

1 to 8 bar (15 to 116 psi) or

0,3 to 1 bar (5 to 15 psi), after removing of the valve body out of the regulator/filter housing

**Water inlet:** Opaque hose with 6 mm external diameter/4 mm internal diameter

**Water outlet:** Hose with 6 mm external diameter/4 mm internal diameter

**Water temperature:** 10 to 40 °C; 50 to 104°F