

Testomat® EVO TH

LENNTECH

info@lennotech.com Tel. +31-152-610-900

www.lennotech.com Fax. +31-152-616-289



The **Testomat® EVO TH** automatically determines the water hardness by titration. It was developed from the **Testomat ECO®** and will provide you with a lot of new functions additionally to the approved functions which are: integrated SD card, firmware update via SD card and data transmission via WLAN access point and many more.

Application

- water treatment plants
- industrial boilers
- monitoring of process water
- drinking water plants

Measuring range

0.05-25 °dH water hardness
(depending on the choice of the indicator)

Technical Data

Power supply: 230 VAC, 24 VAC all 50–60Hz or multi voltage power supply unit 100-240 VAC / 100-353 VDC

Power consumption: max. 30 VA

Protection class: I

Degree of protection: IP 65

Ambient temperature: 10–40 °C, 50 - 104°F

Dimensions (B x H x T): 380 x 480 x 280 mm

Weight: approx. 9.0 kg

Menu languages: German, English, French, Dutch (others upon request)

Mains water supply

Operating pressure:

1 to 8 bar (15 to 116 psi) or

0,3 to 1 bar (5 to 15 psi), after removing of the valve body out of the regulator/filter housing

Water inlet: Opaque hose with 6 mm external diameter/4 mm internal diameter

Water outlet: Hose with 12 mm internal diameter

Water temperature: 10 to 40 °C; 50 to 104°F